

## MODULAR ELECTRIC DECK OVEN **LFM-D**

### Features

- ◆ Durable Stainless Steel construction.
- ◆ Self Contained Steam System produces ample steam for any bakery application.
- ◆ Available in a variety of configurations, from 1 to 4 deck, 2 to 24 pans (standard).
- ◆ Stackable Design allows for quick and clean installation.
- ◆ Compact Size for inclusion in tight work spaces.
- ◆ Individual Deck Controls are easy to use and allow you to bake a wide range of product simultaneously.
- ◆ Excellent Thermal Insulation for installations at near zero clearance.
- ◆ Sturdy 6" Wheels makes service accessibility a breeze.
- ◆ Modern aesthetic design makes it a great showpiece for the front of the house, attracting customers.
- ◆ Sturdy Base with Pan Storage included.
- ◆ Electric is 220v / 3Ph / 60Hz standard. Other voltages are available for order.

### Options & Accessories

- ◆ Steam Collection Hood available with or without Exhaust Fan.
- ◆ 7" Programmable Touch Screen Control Panel
- ◆ 5 Deck Configurations available for order.



Model LFM-D-2T-3  
with optional Hood & Touch Screen Control Panel

### Fast, Practical and Easy to Use!

The new **Empire LFM-D Modular Electric Deck Oven** is a bakers dream! Clean European design emanates a combination of advanced technology and elegant form. Featuring quick installation, compact size and premium quality materials, the **LFM-D** also boasts state of the art heating elements use as little as 11 Kw of power, even while producing steam. The oven's hearth is one of the highest quality baking stones available today, giving you perfect artisan results each and every time. The well designed digital controls are extremely easy to use, and its thermal insulation is so effective, the **LFM-D** can be installed at zero clearance against a wide range of materials. All of this and more makes the **LFM-D Modular Electric Deck Oven** one of the most versatile Electric Deck Ovens on the market today!


# Technical Data

## MODULAR ELECTRIC DECK OVEN LFM-D

| Model              | Overall Dimensions |       |        |                         | Net Capacity<br># of trays | Deck Dimensions |       |               | Deck Capacities |                         |                   | Power |        | Weight<br>lbs |
|--------------------|--------------------|-------|--------|-------------------------|----------------------------|-----------------|-------|---------------|-----------------|-------------------------|-------------------|-------|--------|---------------|
|                    | Width              | Depth | Height | Height w/<br>Hood & Fan |                            | Width           | Depth | Usable Height | Surface Area    | Equivalent Pan Capacity | Approx 1lb Loaves | Kw    | Amps*  |               |
|                    | in                 | in    | in     | in                      |                            | in              | in    | in            | sq/ft           |                         |                   |       |        |               |
| LFM-D-2T-1         | 52.4               | 50.4  | 55.5   | 73.7                    | 2                          | 40.2            | 33.5  | 7.1           | 9.4             | 2.9                     | 16                | 11    | 31.79  | 761           |
| <b>LFM-D-2T-2</b>  | 52.4               | 50.4  | 67.7   | 85.9                    | 4                          | 40.2            | 33.5  | 7.1           | 18.7            | 5.8                     | 32                | 22    | 63.47  | 1153          |
| <b>LFM-D-2T-3</b>  | 52.4               | 50.4  | 72     | 90.2                    | 6                          | 40.2            | 33.5  | 7.1           | 28.1            | 8.6                     | 47                | 33    | 95.26  | 1516          |
| LFM-D-2T-4         | 52.4               | 50.4  | 84.3   | 102.5                   | 8                          | 40.2            | 33.5  | 7.1           | 37.4            | 11.5                    | 63                | 44    | 127.05 | 1907          |
| LFM-D-2TH-1        | 44.5               | 58.3  | 55.5   | 73.7                    | 2                          | 32.3            | 41.3  | 7.1           | 9.3             | 2.9                     | 16                | 11.5  | 33.22  | 737           |
| <b>LFM-D-2TH-2</b> | 44.5               | 58.3  | 67.7   | 85.9                    | 4                          | 32.3            | 41.3  | 7.1           | 18.5            | 5.7                     | 31                | 23    | 66.44  | 1129          |
| LFM-D-2TH-3        | 44.5               | 58.3  | 72     | 90.2                    | 6                          | 32.3            | 41.3  | 7.1           | 27.8            | 8.6                     | 47                | 34.5  | 99.55  | 1489          |
| LFM-D-2TH-4        | 44.5               | 58.3  | 84.3   | 102.5                   | 8                          | 32.3            | 41.3  | 7.1           | 37.1            | 11.4                    | 63                | 46    | 132.77 | 1881          |
| LFM-D-3T-1         | 68.5               | 44.5  | 55.5   | 73.7                    | 3                          | 56.3            | 27.6  | 7.1           | 10.8            | 3.3                     | 18                | 12.5  | 36.08  | 829           |
| <b>LFM-D-3T-2</b>  | 68.5               | 44.5  | 67.7   | 85.9                    | 6                          | 56.3            | 27.6  | 7.1           | 21.6            | 6.6                     | 37                | 25    | 72.16  | 1271          |
| <b>LFM-D-3T-3</b>  | 68.5               | 44.5  | 72     | 90.2                    | 9                          | 56.3            | 27.6  | 7.1           | 32.4            | 10.0                    | 55                | 37.5  | 108.24 | 1690          |
| LFM-D-3T-4         | 68.5               | 44.5  | 84.3   | 102.5                   | 12                         | 56.3            | 27.6  | 7.1           | 43.2            | 13.3                    | 73                | 50    | 144.32 | 2132          |
| LFM-D-4T-1         | 52.4               | 72    | 55.5   | 73.7                    | 4                          | 40.2            | 55.1  | 7.1           | 15.4            | 4.7                     | 26                | 18.5  | 53.35  | 1032          |
| LFM-D-4T-2         | 52.4               | 72    | 67.7   | 85.9                    | 8                          | 40.2            | 55.1  | 7.1           | 30.8            | 9.5                     | 52                | 37    | 106.81 | 1566          |
| LFM-D-4T-3         | 52.4               | 72    | 72     | 90.2                    | 12                         | 40.2            | 55.1  | 7.1           | 46.1            | 14.2                    | 78                | 55.5  | 160.16 | 2061          |
| LFM-D-4T-4         | 52.4               | 72    | 84.3   | 102.5                   | 16                         | 40.2            | 55.1  | 7.1           | 61.5            | 18.9                    | 104               | 74    | 213.62 | 2596          |
| LFM-D-6T-1         | 68.5               | 72    | 55.5   | 73.7                    | 6                          | 56.3            | 55.1  | 7.1           | 21.5            | 6.6                     | 36                | 21    | 60.61  | 1267          |
| LFM-D-6T-2         | 68.5               | 72    | 67.7   | 85.9                    | 12                         | 56.3            | 55.1  | 7.1           | 43.1            | 13.3                    | 73                | 42    | 121.22 | 1956          |
| LFM-D-6T-3         | 68.5               | 72    | 72     | 90.2                    | 18                         | 56.3            | 55.1  | 7.1           | 64.6            | 19.9                    | 109               | 63    | 181.83 | 2605          |
| LFM-D-6T-4         | 68.5               | 72    | 84.3   | 102.5                   | 24                         | 56.3            | 55.1  | 7.1           | 86.2            | 26.5                    | 146               | 84    | 242.44 | 3293.4        |

\* Amperage calculated at 220V/60Hz/3Ph. Other voltages are available. Inquire for details.

### PAN CONFIGURATIONS



### UTILITIES<sup>1</sup>

|                                       |                       |
|---------------------------------------|-----------------------|
| Water Inlet                           | 1/2" NPT <sup>2</sup> |
| Drain                                 | 3/4" NPT              |
| Steam Exhaust<br>(optional accessory) | 4"                    |

<sup>1</sup>Water and Electrical connections located on the back of the unit.  
<sup>2</sup>Approved water filter and pressure regulator required to ensure proper performance.

### LIMITED WARRANTY

This product is warranted to the original purchaser to be free from material and workmanship defects. This warranty extends for a period of one (1) year from the date of purchase on parts and labor and 90 days on electrical components. For additional information or if you have any questions, please do not hesitate to contact us toll free at 1-800-878-4070.

Please note, specifications are subject to change without notice as we continually work to improve our equipment.